

Mach

Touring Series



Specification

	M10CT	M12CT	M15CT	M181Tmk2	M218Tmk2
Power rating AES	250 watt	400 watt	500 watt	900 watt	1800 watt
Power rating peak	500 watt	800 watt	1000 watt	3600 watt	7200 watt
Sensitivity 1w/1m	96 dB	97 dB	98 dB	97 dB	100 dB
Max SPL,calculated long term	120 dB	125 dB	130 dB	133 dB	136 dB
Max SPL, peak	125 dB	131dB	133 dB	137 dB	140 dB
Frequency range ±3dB	80Hz – 20kHz	57Hz – 20kHz	60Hz – 20kHz	30Hz – 250Hz	35Hz – 250Hz
Nominal impedance	8 Ω	8 Ω	8 Ω	8 Ω	2 x 8 Ω
Recommended Amplifier	400 watt,8Ω	600 watt,8Ω	650 watt,8Ω	1200 watt,8Ω	2400 watt,8Ω
Dirsprsion V/H	90° x 70°	90° x 70°	90° x 40°	-	-
Drivers	10" woofer, 1" HF	12" woofer, 1" HF	15"woofer, 1.4"HF	1 x 18" woofer	2 x 18"woofer
Dimensions (HxWxD)mm	480 x 358 x 295	570 x 382 x 348	725 x 492 x 400	590 x 590 x 730	1050 x 590 x 720
Net weight	16 kg (35.3 lbs)	19 kg (41.9 lbs)	30 kg (66.2 lbs)	37 kg (81.5 lbs)	68 kg (150 lbs)
Connectors	2 x Speakon NL-4	2 x Speakon NL-4	2 x Speakon NL-4	2 x Speakon NL-4 (1+ 1-)	2 x Speakon NL-4 (1+ 1- / 2+ 2-)
Order Information	P/N 95101020	P/N 95101220	P/N 95101520	P/N 95101052	P/N 95101062

* Specifications are subject to change without notice.

Authorized distributor:

Mach Audio Ltd.

www.mach-audio.com

info@mach-audio.com